

High Bright Indoor Digital Signage Displays

MITSUMARU
Smart Digital Signage



Features :

- 1500nit, High Bright, LCD Signage Displays
- Sizes Available: 55", 65", 75"
- 4K Resolution
- 9mm Slimline Bezels
- Landscape / Portrait Orientations
- Android OS
- Operational Parameters: 22/7
- 3 Year Commercial Warranty

· **Note: Displays are not to be exposed to direct sunlight.**



High Brightness



Technical Specifications

Panel

	55MISP15UA	65MISP15UA	75MISP15UA
Panel Size	55"	65"	75"
Active Display Area (W x H mm)	1210 x 680	1428 x 803	1650 x 928
Resolution	1920 x 1080	3840 x 2160	3840 x 2160
Aspect Ratio	16 : 9	16 : 9	16 : 9
Brightness	1500	1500	1500
Bezels (T / L / R / B)	9 mm	9 mm	9 mm
Android OS	Yes	Yes	Yes
Viewing Angle (H/V)	178° / 178°		
Backlight Configuration	Direct LED		
Operational Life Cycle - MTBF	50,000 Hours		

Power

Input Voltage	100 VAC / 240 VAC, 50 / 60 Hz					
Max Power Consumption (w)	60	100	140	170	260	500

High Bright Indoor Digital Signage Displays



Technical Specifications

Enclosure

	55MISP15UA	65MISP15UA	75MISP15UA
IP Rating	N/A		
Enclosure Material	Light Weight Steel Fine Grain Powder Coated (Black RAL 9005)		
Glass Type	Tempered Glass Panel		
Glass Characteristics	Transmissivity > 93%, Reflectivity < 2%		
Unit Dimension (W x H x D mm)	1230 x 703 x 56	1450 x 827 x 60	1671 x 952 x 58
Weight (kg)	10.90	16.10	25.10

Environment

Operating Environment	Indoor
Operating Temperature	0°C ~ +40°C
Operating Humidity	10% ~ 80%
Operating Altitude (m)	≤ 2000

Connectivity

CPU	ARM Cortex A55 1.9GHz
GPU	ARM Mali - 450
Memory	4GB
ROM	32GB
HDMI Input	1
USB Input	2
LAN	1
Wi-Fi	802.11 b/g/n

