Product Specification

Product Type: LED All-in-one Display Terminal

Product Model: LA181V11

Product Specification



Product Features

- ◆ Ultra-light and ultra-thin, the weight of a single LED cabinet is only 4.8kg, the thickness is 31mm, no complicated steel structure is needed, which is convenient for construction and installation:
- ◆ Support sound playback, built-in 2*30W audio, support 2.0 channels
- Mobile phone interactive function, support mobile phone to realize touchpad and remote control function, support mobile phone to open application quickly, support mobile phone to adjust display parameters;
- ◆ It supports conference mode, presentation mode, energy saving mode, user mode and multiple modes, and the scene mode can be quickly adjusted according to the application scenario;
- ◆ The full HDMI interface uses HDMI 2.0 interface and supports 4K input;
- Support WiFi function, can be connected to achieve Internet access; support 2.4Gand5Gdual network duplex;
- ◆ Supports Bluetooth function, and can connect to Bluetooth devices via Bluetooth;
- Built-in Android 9.0 system;
- ◆ Built-in 232 and 485 interfaces can realize centralized control function;
- ◆ Full front service, supports hot plug, simplifies maintenance;
- ◆ Leading 3-in-1 integrated board design, which reduces component wired connection and improves stability;
- ◆ Independent R & D design of software and hardware, high compatibility of functional modules, maximize performance of products;
- ◆ Built-in mature technology, support wireless screen sharing, small screen control large screen, letter sending system, timer, built-in "welcome interface" editing software, etc.;
- ◆ Simple and easy-to-use menu, remote control operation; realize brightness, color temperature, contrast, volume and other adjustments, signal source switching, standby mode selection and other functions.
- ◆ Ultra-low standby power consumption design, the standby power consumption of the whole machine is less than 0.5w.
- Meet the EU RoHS directive requirement.

Product Parameter Overall Parameter Size 181 inch Pixel Pitch (mm) P1.58 21:9 Aspect Ratio Resolution 2688x1080 Overall Size (L*H) 4284×1832mm 4270×1715mm Display Area (L*H) Screen Thickness 31mm Net Weight 189kg(wall-mounting bar and stand not included) Recommended Viewing Distance ≥3.2m Maintenance Mode Front Access Installation Mode Wall Mounting / Hanging **Optical Parameter** 550cd/m² **Brightness** Refresh Rate 1920/3840Hz **Gray Scale** 13-16bit Contrast 6500:1 **Color Temperature** 2300-9300K (adjustable) Horizontal 170°, Vertical 170° Viewing Angle ≥100,000hrs LED Lifespan

Electrical Parameter		
Operation Voltage	100-240VAC 50/60Hz	
Standby Power Average Power Consumption of Overall Unit	≤0.5W 0.81KW	
Maximum Power Consumption of Overall Unit	2.38KW	
System Parameter		
Operating System CPU	Android 9.0 Dual Cortex-A72 large core + four Cortex-A53 small core, frequency 2.0GHz	
RAM	4GB	
Storage	32GB	
Media Format	Support mainstream video format such as MPEG1, MPEG2, MPEG4, WMV, MKV, TS, and flv; Support audio formats such as MP3; Support JPG, JPEG, BMP, PNG, GIF and other image format.	
Environmental Parameter		
Operation Temperature	-10°C-40°C	
Operation Humidity	10%-80%RH No condensation	

Note:

- 1. The content of this specification may be adjusted and revised in real time without prior notice to provi de as accurate specification parameters as possible
- 2. This product is an indoor product. It is strictly prohibited to use it in direct sunlight
- 3. In order to ensure long-term and more uniform display effect, do not play fixed images for a long time

I/O Ports

Туре	QTY	
HDMI 2.0 Input	3 (2 internal, 1 external)	
HDMI 2.0 Output	1 (internal)	
USB 2.0	1 (external)	
USB 3.0	1 (external)	
Type C	1 (external)	
3.5 Audio Output	2 (1 internal, 1 external)	
Audio Optical Output	1 (internal)	
RS232 Port	1 (internal)	
RS485 Port	1 (internal)	
Bluetooth	1 (wireless)	
LAN	1 (internal)	

Introduction to button and interface



NO.	Description		
1	Light Sensor		
2	IR		
3	Type C		
4	USB3.0		
5	USB2.0		
6	Menu button (including brightness, color Temperature, contrast, sound, signal		
	source, test mode and Other sub-menus)		
7	Bright/OK (1.When the menu is Not called up, it is the brightness adjustment		
	button,and the + and - keys are used to adjust the brightness; 2.When the		
	menu is called up, it is used as confirm button.)		
8	1.In the brightness adjustment mode, it is the brightness reduction key;		
	2.When the Menu is called up,it is the Down/minus key		
9	1.In the brightness adjustment mode,it is the brightness increase key;		
	2.When the menu Is called up,it is the Up/Add key		
10	Standby/Wake up button		
11	Dual-color indicator light (red/blue)		
12	HDMI input (facedown)		
13	3.5 Audio output port (facedown)		

Introduction to remote control				
Buttons	Introduction			
Q	Standby/Wake up			
	Up			
	Down			
	Confirm			
	Left			
	Right	3 A E		
+	Voice +			
-	Voice -			
J	Back			
Ö	Brightness Adjustment			
=	Channel Switch			
0	Main Interface			

Accessories	
Remote Control	1
Front Maintenance Tool	1
Tool kit	1
Wall-mounting Bar	1
Standing Accessory	1set (optional)

Packing Dimension		
Item	Dimension	Quantity
Cabinet Packing Dimension	1900*1000*900mm	1
Module Packing Dimension	1170*770*875mm	1
Lower Frame and Wall-mounting Bar Packing Dimension	1980*470*380mm	1

Note:

• In case of special requirements, the packing quantity, weight and dimension may change, and the actual product received shall prevail.

Special Statement

- ◆ Intellectual Property Rights: The hardware design and software programs of this product are protected by copyright. The contents of this product and the manual shall not be copied with out the authorization of the company.
- ◆ The contents of this manual are for reference only and do not constitute a commitment of any kind.
- ◆ The company reserves the right to make improvements and changes to the product design without prior notice
- ◆ Note: HDMI, HDMI HD Multimedia Interface and HDMI logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.