# WIRELESS ME TX

## TRANSMITTER FOR THE WIRELESS ME

The Wireless ME TX is an ultra-compact wireless transmitter that makes recording professional audio for your videos effortless – perfect for expanding a RØDE Series IV wireless system. It features both a 3.5mm TRS input for connecting external microphones like lavaliers or VideoMics, along with a built in omnidirectional mic, and thanks to the intelligent GainAssist technology, you can simply clip it onto your subject to be recording crystal-clear wireless audio in seconds.

**Note:** This product requires a RØDE Series IV RX (receiver) to operate, such as the Wireless ME RX, Wireless GO II RX, RØDECaster Pro II, RØDECaster Duo or Streamer X.

- Simple-to-use wireless transmitter for the RØDE Series IV wireless system
- Series IV 2.4 GHz digital transmission for crystal-clear recording with over 100m range
- Intelligent GainAssist technology automatically adjusts volume levels on-the-fly
- High-quality, built-in omnidirectional microphone

- 3.5mm TRS input for connecting external lavalier microphones or VideoMics
- In-built rechargeable lithium-ion battery up to 7 hours battery life
- Requires a RØDE Series IV receiver to operate (including Wireless ME RX, Wireless GO II RX, RØDECaster Pro II, RØDECaster Duo or Streamer X)









#### **ACOUSTIC & ELECTRICAL SPECIFICATIONS**

Acoustic Principle:	Pre-polarised pressure transducer
Polar Pattern:	Omnidirectional
Frequency Range:	20Hz – 20kHz
Dynamic Range:	100dB
Max SPL:	122dB SPL
Equivalent Noise (dBA):	22dBA
Analog Inputs:	TRS (lavalier microphone input)
Connectivity:	USB-C
Bit Depth:	24-bit
Sample Rate:	48 kHz
Minimum Operating Systems Requirements:	mac OS 10.15 above Windows 10 and above iOS 14 Android 11
Power Requirements:	In-built rechargeable lithium-ion battery charged via 5V USB
Operating Time:	7 hours
Transmission Range:	>100m (line of sight)



### MECHANICAL SPECIFICATIONS

#### WHATS IN THE BOX

Weight (grams):	32
Dimensions (millimetres):	Length: 44 Width: 45.3 Height: 18.3
Included Accessories:	2 x Furry Windshield 1 x SC22, 30cm USB-C to USB-C cable
RØDE Software Compatibility:	RØDE Central RØDE Connect RØDE Reporter RØDE Capture



Wireless ME Transmitter (TX)






Furry Windshield

SC22


## DIMENSIONS







## POLAR PATTERN



#### FREQUENCY RESPONSE

