

Yealink RoomSensor is an enterprise multifunctional room sensor integrated with occupancy,temperature,humidity and light detecting functions.Linkage with Yealink RoomPanel through BLE protocol and brings with featurers such as automatic release, automatic checkin, etc. The Passive infrared technology makes motion-detection more excellent and accurate; Lower power consumption & replaceable lithium battery, provide a maximum 5 years life; Wireless application and adjustable angle designing, easy to be installed on all kinds of surface, it can cover whole meeting room easily; Support real-time monitoring of device operation, provides one-stop management through Yealink WorkSpace Platform.

# Key features and benefits



# Passive Infrared

Passive Infrared Technology, high-accuracy room ocuppancy status sensing.



# Temperature Detection

Room temperature detecting,automatically wake up the air conditioner.



### Wireless Installation

Wireless and compact designing, support multi-type surface of wall installation.



# **Humidity Detection**

Room humidity detecting, bring pleasant environment adjustment.



### **Magnetism Designing**

No wired running and magnetism mounted, easy to maintain.



# Light Detection

Room light detecting, associated with the dimmer/switcher adjustment.



### Adjustable Angle

Support ± 20° adjustable angle ,make deployment more simple.



### Device Management over Cloud Server

Easily monitor, manage and diagnose by Yealink WorkSpace Management Cloud Server.



# Lithium Power Supply

Lithium battery power supply, up to 5 years life, userreplaceable part.



# Bluetooth BLE

Directly connect to RoomPanel without extra gateways, ultralow power consumption.



# Status Alarm

Support automatic alarm of abnormal equipment and battery status.



# **Actions with Yealink RoomPanel**

Actions with the Yealink RoomPanel, supports automatic reserve, automatic release, automatic alarm etc.



# **Specifications**

### Basic

- · Detection:
  - Occupancy
  - Temperature
  - Humidity
  - Light
- · Housing: PC, White

#### Sensor

- Occupancy Type: Passive Infrared Tech
- PIR Detection angle: 120°
- Sensor Adjustable angle: ± 20°
- PIR Coverage (Standard 3m/9.8 ft mouting height): 6m/19.7 ft radius (major motion); 3m/9.8 ft radius (minor motion)
- Temp measuring range: -10~70°C
- Humidity measuring range:0~80% RH

#### Communication

- Protocol: Bluetooth BLE 5.2
- Frequency band: 2.4GHz
- Reach: Max. 30m (100 ft)
- Multi-connectivity: Maximum 4 simultaneously, BLE mesh

### Power Supply

- Power supply: 3 V (1\*CR123A lithium battery)
- · Battery life: 5 Year

### Indicator

- Button: 1 x config button
- Led: 1 x LED

### Operating Environmental

• Temperature range: 0~40°C

• Humidity: 10~95%,non-condensing

### IP Rating

• IP Rating: IP20

### Dimension&Weight

- Dimensions: Φ95.3mm\*36mm
- Weight: 0.092KG(0.203lb)

### Mount

- Bracket: Circular mounting bracket, Magnetic Design
- · Mounting: Ceiling/Wall Mounted

### Management

- Yealink Management Cloud Service
- · Yealink Device Management Platform